

Project _____
 Item _____
 Quantity _____
 FCSI section _____
 Approval _____
 Date _____

Model

ConvoVent 4 condensation hood



Standard Features

- Efficient reduction of steam and vapour from the Convotherm 4 combi steamer and grease removal by 3-stage filter design
- Fully automatic control by the Convotherm 4 combi steamer with regulation of the condensing level according to need (2 fan speeds)
- Highly efficient air-to-air heat exchanger technology for energy-saving condensing with zero water consumption
- Built-in connection to the Convotherm 4 wastewater system with condensate drained via air vent
- Filters accessible from front or top for easy cleaning / maintenance
- Baffle filters and mist collectors can be washed in the dishwasher
- Available for all electric Convotherm 4 models
- Also available for fitting on a stacking kit (two Convotherm 4 units placed one above the other)

Accessories

- Built-in halogen lamps (2x15W) to provide front lighting for the Convotherm 4
- Built-in front condenser (no extra space required) for highly effective condensing of escaping vapor when the appliance door is opened

Dimensions and weights

Part number	3455870
For combi steamers of size	C4 6.10 / 10.10
Dimensions	
Width x Depth x Height	877 x 1085 x 240 mm
Weights	
Net weight*	66 kg
Weight including packaging	72 kg

* Additional weight of optional front condenser 6.8 kg.

Part number	3455871
For combi steamers of size	C4 6.20 / 10.20
Dimensions	
Width x Depth x Height	1122 x 1285 x 240 mm
Weights	
Net weight*	96 kg
Weight including packaging	103 kg

* Additional weight of optional front condenser 9.5 kg.

Part number	3455872
For combi steamers of size	C4 20.10
Dimensions	
Width x Depth x Height	892 x 1086 x 240 mm
Weights	
Net weight*	67 kg
Weight including packaging	73 kg

* Additional weight of optional front condenser 6.8 kg.

Part number	3455873
For combi steamers of size	C4 12.20 / 20.20
Dimensions	
Width x Depth x Height	1137 x 1285 x 240 mm
Weights	
Net weight*	97 kg
Weight including packaging	104 kg

* Additional weight of optional front condenser 9.5 kg.

Dimensions and weights, stacking-kit model

Part number	3455874
For appliance combination	C4 6.10 / 10.10

Dimensions

Width x Depth x Height	877 x 1085 x 240 mm
------------------------	---------------------

Weights

Net weight*	68 kg
Weight including packaging	74 kg

* Additional weight of optional front condenser 6.8 kg.

Part number	3455875
For appliance combination	C4 6.20 / 10.20

Dimensions

Width x Depth x Height	1122 x 1285 x 240 mm
------------------------	----------------------

Weights

Net weight*	100 kg
Weight including packaging	107 kg

* Additional weight of optional front condenser 9.5 kg.

Electrical supply

Electrical supply*

Rated voltage	1N~ 200-240V 50/60Hz
Rated power consumption	130-260 W
Rated current	1.0-1.9 A
Fuse	2.5 A

* Mains electrical supply required at customer's site

Safety clearances for installation*

Left-hand side	50 mm
Rear	100 mm
Top*	500 mm

* Depends on type of air ventilation system and nature of ceiling.

Air flow rate

Part number	3455870
	3455872
	3455874

Reduced speed 550 m³/h

Full speed 675 m³/h

Part number	3455871
	3455873
	3455875

Reduced speed 630 m³/h

Full speed 840 m³/h

Noise emission

Part number	3455870
	3455872
	3455874

Measured value 64 db (A)

Part number	3455871
	3455873
	3455875

Measured value 63 db (A)

Certificates

Approval mark	CE, CB, TÜV GS
Degree of protection	IPX 5

Please observe the following points:

- This document is to be used solely for planning purposes.
- Please refer to the ConvoVent 4/4+ installation instructions for further technical data and guidance on installation and positioning.