

Model

ConvoVent 4+ condensation hood



Standard Features

- Efficient condensing of steam and vapour from the Convotherm 4 combi steamer
- Especially effective filtering of odour-bearing or grease-laden particles thanks to the 3-stage filter design with fine-particle filter
- Fully automatic control by the Convotherm 4 combi steamer with regulation of the condensing level according to need (2 fan speeds)
- Highly efficient air-to-air heat exchanger technology for energy-saving condensing with zero water consumption
- Built-in connection to the Convotherm 4 wastewater system with condensate drained via air vent
- Filters accessible from front for easy cleaning / maintenance
- Baffle filters and mist collectors can be washed in the dishwasher
- Available for all electric Convotherm 4 models
- Also available for fitting on a stacking kit (two Convotherm 4 units placed one above the other)

Accessories

- Built-in halogen lamps (2x15W) to provide front lighting for the Convotherm 4

Dimensions and weights

Part number	3455876
For combi steamers of size	C4 6.10 / 10.10
Dimensions	
Width x Depth x Height	877 x 1085 x 373 mm
Weights	
Net weight	85 kg
Weight including packaging	91 kg

Part number	3455877
For combi steamers of size	C4 6.20 / 10.20
Dimensions	
Width x Depth x Height	1122 x 1285 x 373 mm
Weights	
Net weight	119 kg
Weight including packaging	127 kg

Part number	3455878
For combi steamers of size	C4 20.10
Dimensions	
Width x Depth x Height	892 x 1086 x 373 mm
Weights	
Net weight	86 kg
Weight including packaging	92 kg

Part number	3455879
For combi steamers of size	C4 12.20 / 20.20
Dimensions	
Width x Depth x Height	1137 x 1285 x 373 mm
Weights	
Net weight	120 kg
Weight including packaging	128 kg

Dimensions and weights, stacking-kit model

Part number	3455880
For appliance combination	C4 6.10 / 10.10

Dimensions

Width x Depth x Height	877 x 1085 x 373 mm
------------------------	---------------------

Weights

Net weight	87 kg
Weight including packaging	93 kg

Part number	3455881
For appliance combination	C4 6.20 / 10.20

Dimensions

Width x Depth x Height	1122 x 1285 x 373 mm
------------------------	----------------------

Weights

Net weight	123 kg
Weight including packaging	131 kg

Electrical supply

Electrical supply*

Rated voltage	1N~ 200-240V 50/60Hz
Rated power consumption	130-260 W
Rated current	1.0-1.9 A
Fuse	2.5 A

* Mains electrical supply required at customer's site

Safety clearances for installation*

Left-hand side	50 mm
Rear	100 mm
Top*	500 mm

* Depends on type of air ventilation system and nature of ceiling.

Air flow rate

Part number	3455876
	3455878
	3455880

Reduced speed	390 m³/h
Full speed	500 m³/h

Part number	3455877
	3455879
	3455881

Reduced speed	590 m³/h
Full speed	795 m³/h

Noise emission

Part number	3455876
	3455878
	3455880

Measured value	63 db (A)
----------------	-----------

Part number	3455877
	3455879
	3455881

Measured value	62 db (A)
----------------	-----------

Certificates

Approval mark	CE, CB, TÜV GS
Degree of protection	IPX 5

Please observe the following points:

- This document is to be used solely for planning purposes.
- Please refer to the ConvoVent 4/4+ installation instructions for further technical data and guidance on installation and positioning.